

Edgepave

Technical Information	
	 <p>EDGEPAVE 60</p>
Length x Width x Height (mm)	330 x 330 x 60
Pack dimensions (mm)	990 x 990 x 870
Dimensional category	DPB1
No per pack	108
Approximate number per m ² (including joint)	9
Approximate m ² coverage per pack	12.0
Number per lineal m (including joint)	3
Approximate lineal m/pack (including joint)	36
Approximate unit weight (kg)	13.5
Approximate pack weight (kg)	1,026
Unconfined compressive strength (MPa)	> 15
Average characteristic breaking load (kN)	> 10
24 hour cold water absorption (%)	< 8
Impact abrasion resistance (cm ³)	< 10
Slip/skid resistance (BPN)	> 65
Slip resistance category	W
Salt attack resistance category	Exposure
Liability to efflorescence	Nil to Slight



Edgepave

Granite Collection



TUNDRA



SEA MIST



STORM CLOUD



ARCTIC



CHERT



PEBBLE BEACH

Stonewash Collection



SILVER



GREY



CHARCOAL

All Brikmakers' specifications testing is carried out in accordance with Australian/New Zealand Standards AS/NZS 4456 test methods where applicable.

This technical information represents average properties obtained from production lots. If specific test results are required, samples should be taken from current production lots. Durability classification is based on product knowledge under Perth, Western Australia climatic conditions.

To ensure the performance of the pavement and in particular trafficable pavements, it is recommended that square paving units are laid in staggered bond or a 45° staggered bond laying pattern. Rectangular and interlocking paving units should be laid in a herringbone pattern. Please refer to our information on expansion joints when installing large format paving units. It is also important to include 10mm control joints in these pavements.

Sizes and number per square metre or tonne are nominal only and subject to variance due to installation technique, raw material and allowable size variations exhibited by the product.

The physical properties of the Permeable Pavers are indicative and variations in pavement performance will occur depending on unit size and laying pattern. Infiltration rate will vary depending on age of pavement and maintenance schedule of the pavement.

Information is subject to change without notice. All colours are indicative only.

Please confirm all technical, colour and installation specifications are applicable to your application.