



Landscaping Series

Technical Information	 Pier Block	 Masonry Block
Product Codes	LB350	BLK10.31
Colours	Limestone / Natural Earth	Charcoal / Natural Oxide / Grey
Available profile	Plain	Plain
Length x Width x Height (mm)	350 x 165 x 350	390 x 90 x 190
No per pallet	30	108
Approximate number per m ² (including mortar joint)	7.6	12.5
Approximate unit weight (kg)	40	16
Approximate pallet weight (kg)	1,200	1,728
Weight per m ²	305	188
Average compressive strength (MPa)	> 5	> 10
Average block density (kg/m ³)	> 1800	> 1800
Co-efficient of contraction (mm/m/15yrs)	< 0.8	< 0.8
Salt attack resistance category	Exposure	Exposure

 **1300 360 344**

 **www.brikmakers.com**

 **info@brikmakers.com**

All testing is carried out in accordance with Australian/New Zealand Standards AS/NZ4456 or RLMBA industry specification test methods where applicable. Durability classification is based on product knowledge under Perth, Western Australia climatic conditions. This technical information represents average properties obtained from production lots. If specific test results are required, samples should be taken from current production lots. Information is subject to change without notice. All colours are indicative only.

- Note:
- Sizes and number per square metre or tonne are nominal only and subject to variance due to installation technique, raw and size variations through manufacturing process.
 - Retaining wall blocks have one purpose made face.
 - Mortar mix recommendation (C:L:S) for M3 application 1:1:6 M4 application 1:0:4.
 - Efflorescence is a white powdery deposit that may form on the blocks. It is harmless and appears on the blocks due to external salt sources from surrounding materials such as water, mortar, concrete or salty soils.
 - Due to the characteristic nature of the raw materials surface texture variation on the face of the product will vary from block to block and between product runs.
 - Ensure any specification or application issues are addressed with Brikmakers prior to order placement.
 - RLR Blocks will vary in colour within and between batches.

Please confirm all technical, colour and installation specifications are applicable to your application.